

# FTPC6V-FP series

6W LED Switching Power Supply



## ■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Overload / Over temperature
- Compliance to ERP directive
  - lifetime 30000hrs.
  - IP44



## Ⓢ ELECTRICAL SPECIFICATION

| MODEL                                   | FTPC6V12-FP   | FTPC6V24-FP |
|---|---|-------------|
| <b>OUTPUT</b>                           |   |             |
| <b>Rated Voltage</b>                    | 12V   | 24V         |
| <b>Rated Current</b>                    | 0.5A  | 0.25A       |
| <b>Current Range</b>                    | 0.0 ÷ 0.5A  | 0.0 ÷ 0.25A |
| <b>Rated Power</b>                      | 6W  | 6W          |
| <b>No Load Output Voltage (max.)</b>    | 11.96V  | 23.97V      |
| <b>Line Regulation</b>                  | ± 1%  |             |
| <b>Load Regulation</b>                  | ± 2%  |             |
| <b>Voltage Tolerance [3]</b>            | ± 5%  |             |
| <b>Ripple &amp; Noise (max.) [2]</b>    | 200mV <sub>p-p</sub>  |             |
| <b>Setup, Rise Time [4]</b>             | 17.5ms, 18ms / 230VAC at full load  |             |
| <b>Hold up Time (typ.)</b>              | 17ms / 230VAC at full load  |             |
| <b>INPUT</b>                            |   |             |
| <b>Voltage Range</b>                    | 180 ÷ 264VAC  |             |
| <b>Frequency Range</b>                  | 47 ÷ 63Hz   |             |
| <b>Power Factor (typ.)</b>              | PF > 0.6 / 230VAC at full load  |             |
| <b>Efficiency (typ.)</b>                | 75%   | 75%         |
| <b>AC current (typ.)</b>                | 0.04A / 230VAC  |             |
| <b>Inrush current (max.)</b>            | <60A / 230VAC (25°C)  |             |
| <b>No Load Power Consumption (max.)</b> | < 1W  |             |
| <b>PROTECTIONS</b>                      |   |             |
| <b>Over Current</b>                     | Range: > 160%   |             |
|   | Type: hiccup mode. Recovers automatically after fault condition is removed. |             |
| <b>Short Circuit</b>                    | Type: hiccup mode. Recovers automatically after fault condition is removed. |             |

# FTPC6V-FP series

6W LED Switching Power Supply



## WORKING ENVIRONMENT

|   |   |
|---|---|
| <b>Working Temperature</b>              | -20°C ÷ +45°C                             |
| <b>Working Humidity</b>                 | 45 ÷ 85% RH non-condensing                |
| <b>Storage Temperature and Humidity</b> | -30°C ÷ +80°C, 10 ÷ 95% RH non-condensing |

## SAFETY AND EMC REGULATIONS

|                          |  |
|--------------------------|--|
| <b>Safety Standards</b>  | Compliance to EN61347-1, EN61347-2-13  |
| <b>Withstand Voltage</b> | IN/OUT: 3.75kVAC                       |
| <b>EMC Emission</b>      | Compliance to EN55015                  |
| <b>EMC Immunity</b>      | Compliance to EN61547                  |
| <b>Harmonic Current</b>  | Compliance to EN61000-3-2, EN61000-3-3 |

## OTHERS

|                           |                             |
|---------------------------|-----------------------------|
| <b>Dimensions</b>         | 132 x 52 x 12mm (L x W x H) |
| <b>Weight and Packing</b> | 0.2kg; 50pcs./box           |

EAN Code



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

## © MECHANICAL SPECIFICATION

