

FTPC75V-FP series

75W LED Power Supply (CV)



■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Overload / Over temperature
- Cooling by free air convection
- Compliance to worldwide regulations for lighting
- IP44 protection level



ELECTRICAL SPECIFICATION

MODEL	FTPC75V12-FP	FTPC75V24-FP
OUTPUT		
RATED VOLTAGE	12V	24V
RATED CURRENT	6.25A	3.13A
CURRENT RANGE	0 ÷ 6.25A	0 ÷ 3.13A
RATED POWER	75W	75W
NO LOAD OUTPUT VOLTAGE (MAX.)	12.6V	25.2V
LINE REGULATION	± 0.5%	± 0.5%
LOAD REGULATION	± 1%	± 1%
VOLTAGE TOLERANCE [3]	± 5%	± 5%
RIPPLE & NOISE (MAX.) [2]	180mV _{p-p}	250mV _{p-p}
SETUP [4]	300ms / 230VAC at full load	
HOLD UP TIME (MIN.)	5ms / 230VAC at full load	

INPUT

VOLTAGE RANGE	180 ÷ 264VAC	
FREQUENCY RANGE	50 ÷ 60Hz	
POWER FACTOR (MAX.)	0.9 / 230VAC	
EFFICIENCY (MAX.)	90%	90%
AC CURRENT (TYP.)	0,5A / 230VAC	
INRUSH CURRENT (MAX.)	<75A / 230VAC(25°C)	
NO LOAD POWER CONSUMPTION (MAX.)	0.21W	

PROTECTIONS

OVER CURRENT	140%
	Type: hiccup mode. Recovers automatically after fault condition is removed.
SHORT CIRCUIT	Type: hiccup mode. Recovers automatically after fault condition is removed.
OVER TEMPERATURE	Range: IC detect temperature
	Type: shut down output voltage. Re-power on to recovery

FTPC75V-FP series

75W LED Power Supply (CV)



WORKING ENVIRONMENT

WORKING TEMPERATURE	-20°C ÷ +45°C
WORKING HUMIDITY	45 ÷ 85% RH
STORAGE TEMPERATURE AND HUMIDITY	-30°C ÷ +70°C, 10 ÷ 95% RH non-condensing

SAFETY AND EMC REGULATIONS

SAFETY STANDARDS	Compliance to EN61347-1, EN61347-2-13
WITHSTAND VOLTAGE	IN/OUT: 3.75kVAC
EMC EMISSION	Compliance to EN55015
EMC IMMUNITY	Compliance to EN61547; EN61000-4-2, 3, 4, 5, 6
HARMONIC CURRENT	Compliance to EN61000-3-2

OTHERS

INPUT WIRES	H05VVH2-F 2*1.0mm ² , Length = 15cm ± 3cm
OUTPUT WIRES	H03VVH2-F 2*0.75mm ² , Length = 15cm ± 3cm
DIMENSIONS	172 x 59.5 x 18.5mm (L x W x H)
WEIGHT AND PACKING	0.26kg; 25pcs./carton; carton dimensions: 34 x 20.5 x 18.5cm

EAN Code



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

MECHANICAL SPECIFICATION

